

First Hit

## End of Result Set

☐ [Generate Collection](#) [Print](#)

L1: Entry 3 of 3

File: TDBD

May 1, 1999

TDB-ACC-NO: NNRD421143

DISCLOSURE TITLE: Wake on Access from Cable Modem

PUBLICATION-DATA:

Research Disclosure, May 1999, UK

VOLUME NUMBER: 42

ISSUE NUMBER: 421

PUBLICATION-DATE: May 1, 1999 (19990501)

CROSS REFERENCE: 0374-4353-42-421-0

## DISCLOSURE TEXT:

Problem Solved By This Invention: Cable modem technology is rapidly penetrating US households. Cable modems offer the key benefit of constant connectivity. Because cable modems use connection-less technology, much like an office LAN, a subscriber's PC is always on-line with the network. The only problem is the subscriber's PC is not always turned on. This invention will add a defined protocol that, when transmitted to the subscriber's PC, will power up the PC to receive the packets from the network. Description of Invention: Cable systems were originally designed to deliver broadcast television signals efficiently to subscribers' homes. To ensure that consumers could obtain cable service with the same TV sets they use to receive over-the-air broadcast TV signals, cable operators recreate a portion of the over-the-air radio frequency (RF) spectrum within a sealed coaxial cable line. Traditional coaxial cable systems typically operate with 330 MHz or 450 MHz of capacity, whereas modern hybrid fiber/coax (HFC) systems are expanded to 750 MHz or more. Logically, downstream video programming signals begin around 50 MHz, the equivalent of channel 2 for over-the-air television signals. The 5 MHz - 42 MHz portion of the spectrum is usually reserved for upstream communications from subscribers' homes.

Each standard television channel occupies 6 MHz of RF spectrum. Thus a traditional cable system with 400 MHz of downstream bandwidth can carry the equivalent of 60 analog TV channels and a modern HFC system with 700 MHz of downstream bandwidth has the capacity for some 110 channels. Cable Modem Access Networks To deliver data services over a cable network, one television channel (in the 50 - 750 MHz range) is typically allocated for downstream traffic to homes and another channel (in the 5 - 42 MHz band) is used to carry upstream signals.

A cable modem headend system communicates through these channels with cable modems located in subscriber homes to create a virtual local area network (LAN) connection. Most cable modems are external devices that connect to a personal computer (PC) through a standard 10 Base-T Ethernet card and twisted-pair wiring. The cable modem access network operates at Layer 1 (physical) and Layer 2 (media access control/logical link control) of the Open System Interconnect (OSI) Reference Model. Thus, Layer 3 (network) protocols, such as IP traffic, can be seamlessly delivered over the cable modem platform to end users.

A single downstream 6 MHz television channel may support up to 27 Mbps of downstream data throughput from the cable headend using 64 QAM (quadrature amplitude modulation) transmission technology. Speeds can be boosted to 36 Mbps using 256 QAM. Upstream channels may deliver 500 Kbps to 10 Mbps from homes using 16QAM or QPSK (quadrature phase shift key) modulation techniques, depending on the amount of spectrum allocated for service. This upstream and downstream bandwidth is shared by the active data subscribers connected to a

given cable network segment, typically 500 to 5,000 homes on a modern HFC network. Each cable modem has a unique address. The Wake On Access frame will contain the unique address repeated 16 times.

After that it will have a command packet. The command packet supports multiple actions to the computer including turn on, turn off, and others. The cable modem will have aux power from the power line and the ability to always look at the downstream TV channel which supports the cable modem data. When it sees it's MAC address repeated 16 times it will send a signal to the personal computer to turn on the personal computer power supply and bring the computer up to full operation. There are many examples where this will be beneficial to end users. An example is an end user wants to get the Wall Street Journal. The Wall Street Journal can be transmitted at 36 Mbps within a few minutes. The entire Journal would then be stored on the end user hard drive. The problem is you need to ensure the computer is ON to accept the digital Journal for storage on the hard drive. With this invention you would send the Wake on Cable packet first. This would wake up the computer so it would be ready to receive the full Journal. Once the Journal is sent another packet similar to the Wake up packet can turn it off.

SECURITY: Use, copying and distribution of this data is subject to the restrictions in the Agreement For IBM TDB Database and Related Computer Databases. Unpublished - all rights reserved under the Copyright Laws of the United States. Contains confidential commercial information of IBM exempt from FOIA disclosure per 5 U.S.C. 552(b)(4) and protected under the Trade Secrets Act, 18 U.S.C. 1905.

COPYRIGHT STATEMENT: The text of this article is Copyrighted (c) IBM Corporation 1999. All rights reserved.

Pages:68 - 73

[\[Abstract\]](#) [\[PDF Full-Text \(100 KB\)\]](#) IEEE CNF

---

**5 Remote monitoring of cable TV headends**

*Bullinger, R.;*

Broadcasting Convention, 1992. IBC., International , 3-7 Jul 1992

Pages:246 - 250

[\[Abstract\]](#) [\[PDF Full-Text \(180 KB\)\]](#) IEEE CNF

---

**6 A sampled-data switched-current analog 16-tap FIR filter with digitally programmable coefficients in 0.8  $\mu$ m CMOS**

*Yee Ling Cheung; Buchwald, A.;*

Solid-State Circuits Conference, 1997. Digest of Technical Papers. 44th ISSCC., 1997 IEEE International , 6-8 Feb. 1997

Pages:54 - 55, 429

[\[Abstract\]](#) [\[PDF Full-Text \(1240 KB\)\]](#) IEEE CNF

---

**7 Rapid prototyping of a CATV network termination for ATM-based video-on-demand services**

*Vande Keere, V.; Staelens, B.; Vandewege, J.;*

Rapid System Prototyping, 1996. Proceedings., Seventh IEEE International Workshop on , 19-21 June 1996

Pages:44 - 49

[\[Abstract\]](#) [\[PDF Full-Text \(552 KB\)\]](#) IEEE CNF

---

**8 Industrial communication networks parts, pieces, and troubleshooting**

*Bryant, G.;*

Electrical Engineering Problems in the Rubber and Plastics Industries, 1992., IEEE Conference Record of 1992 Forty-Fourth Annual Conference of , 13-14 April 1992

Pages:21 - 24

[\[Abstract\]](#) [\[PDF Full-Text \(292 KB\)\]](#) IEEE CNF


---

[Home](#) | [Log-out](#) | [Journals](#) | [Conference Proceedings](#) | [Standards](#) | [Search by Author](#) | [Basic Search](#) | [Advanced Search](#) | [Join IEEE](#) | [Web Account](#) | [New this week](#) | [OPAC Linking Information](#) | [Your Feedback](#) | [Technical Support](#) | [Email Alerting](#) | [No Robots Please](#) | [Release Notes](#) | [IEEE Online Publications](#) | [Help](#) | [FAQ](#) | [Terms](#) | [Back to Top](#)

Copyright © 2004 IEEE — All rights reserved



Welcome  
United States Patent and Trademark Office


[Help](#) [FAQ](#) [Terms](#) [IEEE Peer Review](#)
[Quick Links](#)

Welcome to IEEE Xplore®

- ☐ Home
- ☐ What Can I Access?
- ☐ Log-out

Tables of Contents

- ☐ Journals & Magazines
- ☐ Conference Proceedings
- ☐ Standards

Search

- ☐ By Author
- ☐ Basic
- ☐ Advanced

Member Services

- ☐ Join IEEE
- ☐ Establish IEEE Web Account
- ☐ Access the IEEE Member Digital Library

Print Format

Your search matched **8** of **1040503** documents.

A maximum of **500** results are displayed, **15** to a page, sorted by **Relevance** in **Descending** order.

#### Refine This Search:

You may refine your search by editing the current search expression or entering a new one in the text box.

☐ Check to search within this result set

#### Results Key:

**JNL** = Journal or Magazine    **CNF** = Conference    **STD** = Standard

#### 1 Improvement of the official examinations for the signal quality of the cable TV systems in Taiwan: the modification of the automatic measurement software

*Bing-Yuh Lu; Yigh-Pyng Lin; Hai-Han-Lu; Hung-Wen Hung; Chin-Yuan Lin; Te-Son Kuo;*

Instrumentation and Measurement Technology Conference, 2000. IMTC 2000. Proceedings of the 17th IEEE , Volume: 1 , 1-4 May 2000  
Pages:473 - 477 vol.1

[\[Abstract\]](#)    [\[PDF Full-Text \(648 KB\)\]](#)    IEEE CNF

#### 2 A single-chip universal burst receiver for cable modem/digital cable-TV applications

*Lu, F.; Min, J.; Liu, S.; Cameron, K.; Jones, C.; Lee, O.; Li, J.; Buchwald, A.; Jantzi, S.; Ward, C.; Choi, K.; Searle, J.; Samueli, H.;*

Custom Integrated Circuits Conference, 2000. CICC. Proceedings of the IEEE 2000 , 21-24 May 2000  
Pages:311 - 314

[\[Abstract\]](#)    [\[PDF Full-Text \(352 KB\)\]](#)    IEEE CNF

#### 3 Digital IF modulator and demodulator design for transmission over band-limited channels

*Wang, X.H.; QViu, X.Z.; Codenic, J.; Vandewege, J.; De Meyer, K.; Trog, W.;*  
Signal Processing, 1996., 3rd International Conference on , Volume: 2 , 14-18 Oct. 1996

Pages:1242 - 1245 vol.2

[\[Abstract\]](#)    [\[PDF Full-Text \(316 KB\)\]](#)    IEEE CNF

#### 4 An object oriented programming approach for hardware design

*Vernalde, S.; Schaumont, P.; Bolsens, I.;*

VLSI '99. Proceedings IEEE Computer Society Workshop On , 8-9 April 1999